

#### **DECLARATION OF PERFORMANCE**

according Annex III of the Regulation (EU) No 305/2011

Name of the product: **BPB**<sup>®</sup> **IMP BI-Super (H)** 

No.: 15/2018

1. Unique identification code of the product-type:

EN 1504-2: ZA.1a

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

### batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

Surface protection products - water-repellent impregnation Protection against the penetration of substances (1.1) Regulation of the moisture content (2.1) Increase of the electrical resistance (8.1)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

REMEI & BPB GmbH & Co. KG Industriestr. 4 D-32825 Blomberg

5. Where applicable, name and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

### not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

#### System 4

(for applications with low performance requirements and which are not subject to fire behavior requirements)

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

## not relevant

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

#### not relevant



9. Declared performance

| Essential characteristics                       | Performance   | Harmonised<br>Technical<br>specification |
|---|---|--|
| Penetration depth<br>EN 1504-2 Tab. 3           | Class: I < 10 mm  |  |
| Drying rate EN 13579                            | Class II: > 10 %  |  |
| Water absorption and alkali resistance EN 13580 | absorptivity < 7,5 %, compared to the untreated sample, absorptivity < 10 %, after immersion in alkali solution | EN 1504-2:2004                           |
| Testing of the freeze-thaw salt cycles          | NPD   |  |
| Dangerous substances                            | NPD   |  |

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Blomberg, 28 Feb. 24

by order S.Hachmeister Lab Manager by order E. Wagner production Manager

# Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is annexed to this Declaration of Performance.