

# ALGAE REMOVER

Moss- and algae remover  
Product No.: 02000-003x

## Product Information:

### Properties:

– for removing algae organic growth, mildew and moss

### Application:

on porous mineral surfaces such as stone, concrete, plaster or bricks

ALGENENTFERNER (ALGAE REMOVING AGENT) is used for the effective, sustainable removal of moss and algae. By treating the soiled surfaces with ALGENENTFERNER (ALGAE REMOVING AGENT), the organic growth is destroyed and further formation of roots and spores is avoided. If used properly, the surrounding plants will not be damaged.

We recommend the impregnation of the cleaned surfaces to avoid durably a new soiling by moss and algae. We recommend: IMPRÄGNIERUNG PERFECT (IMPREGNATION PERFECT). This impregnation can easily and safely be applied, is of neutral colour and has a long-lasting effect. To remove normal organic growth, ALGENENTFERNER (ALGAE REMOVING AGENT) is diluted with water in the ratio 1:3. The surface to be treated must be absolutely dry.

ALGENENTFERNER (ALGAE REMOVING AGENT) is richly and smoothly sprayed or applied by brush to the dry surface. After approx. 3 - 5 days, the dead algae can easily be loosened with a broom. In case of stronger algae organic growth repeat the application or use ALGENENTFERNER - KONZENTRAT (ALGAE REMOVER CONCENTRATE). Do not dispose of with the household waste! Dispose of product residues in hazardous waste dump or collection points for hazardous substances! Do not allow the material to enter the drainage system, water courses or soil. Keep out of reach of children. Wear chemical resistant gloves. In case of contact with the skin immediately rinse with plenty of water and soap. Hint: Use biocidal products carefully. Always read label and product information before use.

### Composition:

2.9% Quaternary ammonium compounds (BAC C12-16)

Generally conduct a preliminary test to avoid changes in colour of the surface to be treated and to determine the needed quantity.

### Quantities to use:

For the application on surfaces apply 100 - 200 g/m<sup>2</sup>.

### Specifications:

Appearance: liquid  
Colour: blue to colourless  
Density: 1.00 ± 0.02 g/ml

### Registration number:

BAuA reg. no.: N-68515

**Storage:**

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 5 years.

**Packaging:**

container 1,000 kg, drum 210 kg, can 20 kg  
Please ask for further package sizes.

**Safety Rules:**

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166). During cleaning work ensure good ventilation (5 to 15 air changes per hour) or exhaust suction device to use.

Do not mix with other products

Restriction of use for SWITZERLAND

From 1.12.2020, green film removers may only be used in Switzerland for applications on facades, irrespective of the active substance they contain (ChemRRV of 17.4.2019; Annex 2.4, Number 4)

Use on roofs and terraces, on storage areas, on and along roads and railways is prohibited from that date.

**Assistance:**

Please contact our Technical Application Centre.

**Industrial use**

Use biocidal products carefully. Always read label and product information before use.

**Commercial use**

Use biocidal products carefully. Always read the label and product information before use.

**Consumers**

Use biocidal products carefully. Always read the label and product information before use.