

BIOtrenn B 12

Separating agent for metallic surfaces of concrete conveyors
Product No.: 310014000

Product Information:

Properties:

- avoids the sticking of concrete and mortar residues, neither attacks metal nor lacquer
- environmentally friendly, does not build up

Application:

mixers
block machines
tools

A smooth slipping of fresh concrete on metal is ensured. BIoTrenn B 12 shows its full effect where the adhesive power of usual separating agents is not sufficient due to high quantities to be conveyed.

BIOtrenn B 12 is applied with a coating or spraying system (wide jet 0.1 - 0.2 mm) to the clean and dry metal surface. Prior to first application we recommend to remove first possible cement films using cement film remover REBAnit S. Do not allow product to get into the environment uncontrolled.

Quantities to use:

10 - 25 g/m²

Vegetable oils can sometimes have a significant influence on the resistance of certain rubber seals. To be on the safe side, we recommend checking the compatibility of the parts that come into contact before use.

Specifications:

Appearance: liquid
Colour: amber
Density: 0.91 ± 0.02 g/ml

Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months.

Packaging:

container 1000 l, drum 210 l, can 20 l
Please ask for further package sizes.

Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).
When used, ensure good ventilation (5 to 15 air exchange per hour) or exhaust suction device to use.
Do not breathe spray.

Assistance:

Please contact our Technical Application Centre.

Industrial use

Recommended frequency and duration of use:
up to 8 hours / day with local exhaust