

BIOtrenn E 40

Mineral oil-free separating agent for hard-wood pallets
Product No.: 310004000

Product Information:

Properties:

- environmentally friendly, does not build up
- stable water-oil emulsion
- free from organic solvents
- water dilutable (1:10)

Application:

wooden pallets for block machines

It is to be expected that the product can be assessed as "easily biodegradable" due to the used ingredients.

Primarily daily treatment is important, particularly on brand-new pallets. We recommend applying BIOtrenn E 40 automatically with an appropriate spray system. The wooden pallets should be treated at least 10 min. prior to use.

Quantities to use:

20 - 50 g/m², depending on the type and absorbency of the mould

Vegetable oils can sometimes have a significant influence on the resistance of certain rubber seals. To be on the safe side, we recommend checking the compatibility of the parts that come into contact before use.

Specifications:

Appearance: liquid
Colour: white
Density: 0.97 ± 0.02 g/ml

Storage:

Protect against frost, direct sun and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 6 months. If stored at > 30 °C and/or > 2 months, the product has to be stirred prior to use.

Packaging:

container 1000 l, drum 210 l, can 20 l
Please ask for further package sizes.

Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).

When used, ensure good ventilation (5 to 15 air exchange per hour) or exhaust suction device to use.

Do not breathe spray.

Assistance:

Please contact our Technical Application Centre.