

BIOtrenn KS

Biodegradable separating agent for plastic pallets
Product No.: 310005000

Product Information:

Properties:

- does not build up; odourless, solvent- and mineral oil-free separating agent emulsion
- especially for the application on plastic pallets
- water dilutable (1:1 to 1:3)
- aqueous emulsion on vegetable oil basis

Application:

for plastic pallets

It is to be expected that the product can be assessed as "easily biodegradable" due to the used ingredients.

The pallets have to be cleaned thoroughly before applying BIOtrenn KS. Slightly adhering parts should completely be removed by mechanical cleaning with a brush. BIOtrenn KS is applied directly after the board turning device, e. g. by spray application. The whole pallet surface must be covered with a thin separating agent film.

Quantities to use:

15 - 30 ml/m²

Vegetable oils can sometimes have a significant influence on the resistance of certain rubber seals. To be on the safe side, we recommend checking the compatibility of the parts that come into contact before use.

Specifications:

Appearance: liquid
Colour: white
Density: 0.98 ± 0.02 g/ml

Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 6 months. If stored >2 months, the product has to be stirred prior to use. The storage temperature may not exceed 35 °C.

Packaging:

container 1000 l, drum 210 l, can 20 l
Please ask for further package sizes.

Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).
When used, ensure good ventilation (5 to 15 air exchange per hour) or exhaust suction device to use.
Do not breathe spray.

Assistance:

Please contact our Technical Application Centre.