

BIOtrenn Spezial

Separating agent with preservative effect

Industrial use

Product No.: 310025000

Product Information:

Sustainability Assessment:

Vegetable oil based

60% from renewable raw materials

Properties:

- for clean surfaces
- for sharp edges and profiles
- also suitable as mixer protection

Application:

for all types of moulds

especially for steel moulds

block machines

Release agents have hardly any effect on the total of CO₂ emissions and the greenhouse gases produced in the production process.

This effect is attempted to be balanced by using sustainable raw materials.

It is to be expected that the product can be assessed as "easily biodegradable" due to the used ingredients.

The release agent is applied undiluted to the perfectly cleaned formwork using a brush or spray device (wide jet nozzle 0.1-0.2 mm).

Quantities to use:

15 - 50 ml/m²

depending on the type and absorbency of the mould

Vegetable oils can sometimes have a significant influence on the resistance of certain rubber seals. To be on the safe side, we recommend checking the compatibility of the parts that come into contact before use.

Specifications:

Appearance: liquid

Colour: yellow

Density: 0.87 ± 0.03 g/ml

Storage:

Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months

Protect from frost, direct sunlight and contamination.

Packaging:

Container 1000 l, Drum 210 l, Can 20 l

Other delivery quantities on request

Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).

When used, ensure good ventilation (5 to 15 air exchange per hour) or use exhaust device.

Do not breathe spray.

Assistance:

Please contact our Technical Application Centre.

Industrial use:

Recommended frequency and duration of use:
480 minutes/day with local exhaust

Environmental Exposure:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or the sewage system.