

BIOtrenn Super

Special separating agent for non-absorbing moulds
Product No.: 310026000

Product Information:

Properties:

- separating agent for non-absorbing, large-size moulds (+60 °C)
- does not form pores
- for sharp edges and profiles

Application:

for heated moulds up to 60 °C
for solvent resistant plastic moulds

It is to be expected that the product can be assessed as "easily biodegradable" due to the used ingredients.

The non-diluted BIOtrenn Super is applied as thin and even as possible to the mould with a brush, sponge or spray system. The moulds should be dry and clean in order to obtain the full effect of the thin layer. Do not allow product to get into the environment uncontrolled.

Quantities to use:

15 - 30 g/m² for steel moulds
20 - 40 g/m² for plastic moulds

Vegetable oils can sometimes have a significant influence on the resistance of certain rubber seals. To be on the safe side, we recommend checking the compatibility of the parts that come into contact before use.

Specifications:

Appearance: liquid
Colour: yellow
Density: 0.81 ± 0.02 g/ml

Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months.

Packaging:

container 1000 l, drum 210 l, can 20 l
Please ask for further package sizes.

Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).
When used, ensure good ventilation (5 to 15 air exchange per hour) or exhaust suction device to use.
Do not breathe spray.

Assistance:

Please contact our Technical Application Centre.

Industrial use

Recommended frequency and duration of use:
up to 8 hours / day with local exhaust