

# BPB® ACTIVE DETERGENT

Active detergent

## Industrial use

Product No.: 320045000 ! ATTENTION: NEW PRODUCT NUMBER FROM 2024 !

Product No. until 2023: 329010033

## Product Information:

### Properties:

- based on a purely natural solvent
- completely free of aromatics and completely biodegradable
- emulsifies with water
- cleans chewing gum, oil- and grease-polluted surfaces
- suitable to detach latex

### Application:

industrial detergent

The cleaner is a unique natural product. The natural character of the cleaner makes this product humane and renewable. Specially formulated to clean adhesive equipment, tar and bitumen based on purely natural solvents, fully biodegradable.

The detergent is sprayed neat onto the surface to be treated or the objects to be cleaned are immersed.

### Spraying:

Spray the product directly onto the object to be cleaned. Let the cleaner work for some time, then wipe off with a cloth or remove with water under high pressure.

### Immersion method:

Immerse the object to be cleaned in the detergent and let the product take effect for a while. Then let the object drip off and rinse it off with water or blow dry with air pressure.

Always carry out a preliminary test to determine the compatibility of the substrate to be treated and to determine consumption.

### Ingredients:

>= 30% D-Limonene

5 -< 15% nonionic surfactants

### Quantities to use:

100 - 150 ml/m<sup>2</sup>

Depending on application up to optimum cleaning effect. The application can be repeated as often as required until perfect cleaning.

The product may not dry up.

### Specifications:

Appearance: liquid

Colour: green blue

Density: 0.88 ± 0.03 g/ml

Flash point: approx. 58,5 °C

### Storage:

Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months

Protect from frost, direct sunlight and contamination.

### Packaging:

Container 1000 l, Drum 210 l, Bottle 0.6 l

Other delivery quantities on request

**Safety Rules:**

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).

When cleaning, ensure good ventilation (5 to 15 air changes per hour) or use suction devices.

No open flames and light during spraying. Keep away from ignition sources. Test first if used on plastics.

**Assistance:**

Please contact our Technical Application Centre.

**Industrial use:**

Recommended frequency and duration of use:

Roll/Sweep/Spray: 480 minutes/day with local exhaust ventilation

**Environmental Exposure:**

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or the sewage system.