

BPB[®] Detergent T Concentrate

Surfactant-based power cleaner based on renewable raw materials

Consumers

Product No.: 320031000 ! ATTENTION: NEW PRODUCT NUMBER FROM 2024 !

Product No. until 2023: 329010034

Product Information:

Sustainability Assessment:

> 70% surfactants from renewable raw materials

Properties:

– solvent-free

Application:

for all cementitious and mineral building materials and exposed aggregate concrete slabs

The detergent contains a balanced combination of dissolving and cleaning components. It loosens and removes oil and grease dirt, residues from floor care products, self-gloss films, light wax films and stubborn general dirt.

The detergent can be diluted up to 1:20 with water, depending on how dirty it is. For heavier soiling, apply pure or diluted up to 1: 5 with water.

The detergent is applied with a brush, brush or spray device, depending on the cleaning purpose. After an exposure time of approx. 5 - 15 minutes, brush off and pick up.

Rinse well with clear water. Do not let the detergent dry out, if necessary add a little more water and brush off again. When product residues dry on the concrete surface, yellow discolouration forms.

Always carry out a preliminary test to determine the compatibility of the substrate to be treated and to determine consumption.

Ingredients:

< 5 % non-ionic surfactants

< 5 % phosphates

Quantities to use:

10 - 100 g/m²

Depending on application up to optimum cleaning effect. The application can be repeated as often as required until perfect cleaning.

The product may not dry up.

Specifications:

Appearance: liquid

Colour: colorless

Density: 1.02 ± 0.02 g/ml

pH-value: 7.0

Storage:

Under normal storage conditions (closed container, 20 °C) minimum shelf-life 24 months

Protect from frost, direct sunlight and contamination.

Packaging:

Can 20 kg and 5 kg, Bottle 1 kg

Other delivery quantities on request

Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).

When cleaning, ensure good ventilation (5 to 15 air changes per hour) or use suction devices.

Assistance:

Please contact our Technical Application Centre.

Industrial use:

Recommended frequency and duration of use:

Roll/Sweep: 480 minutes/day with local exhaust

Commercial use:

Recommended frequency and duration of use:

Roll/Sweep: 60 minutes

Consumers:

Recommended frequency and duration of use:

Roll/Sweep: 60 minutes

Environmental Exposure:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or the sewage system.

Must not get into the sewage water undiluted or unneutralized.