

# BPB® IMP INTENSIV

Colour intensifier

## Industrial use

Product No.: 410038000 ! ATTENTION: NEW PRODUCT NUMBER FROM 2024 !

Product No. until 2023: 349010045

## Product Information:

### Properties:

- dissolved in organic solvents
- very high penetration properties

### Application:

for compacted concrete and natural stones

The impregnation is absorbed into the surface, making it water-repellent and deepening the natural color and structure. The surfaces look brighter and fresher, almost as if they were wet. The water-repellent effect reduces the tendency to soiling and stain sensitivity and makes cleaning easier. In outdoor areas, depending on the type of stone and weather conditions, the colour-intensifying effect is maintained for approx. 1 - 2 years, the protective effect lasts for approx. 5 - 7 years.

Can be repainted several times when the effect fades.

DO NOT apply to surfaces that have already been impregnated.

The product is supplied ready to use and can be used without further mixing or dilution.

The application is carried out by using a foam roller.

### Drying time:

Walkable after approx. 30 minutes,

Complete drying within 24 hours.

To assess the final effect a testing site on the surface which is representative for the final application is imperative.

### Quantities to use:

200 - 500 ml/m<sup>2</sup>

The specified quantities are approximate values because the actual applied quantity does not only depend on the surface structure, but also on the absorbency of the surface.

Avoid direct sun, dust formation or soiling during application. Do not apply if the forecast says rain during the next 4 hours. Clean tools with thinner.

Application temperature (product and substrate): between +5 °C and +35 °C.

### Please note:

Protect plants, glass, polished surfaces, wooden and varnished surfaces, plastics and other sensitive surfaces against splashes.

### Specifications:

Appearance: liquid

Colour: colourless

Density: 0.80 ± 0.03 g/ml

### Storage:

Under normal storage conditions (closed container, 20 °C) minimum shelf-life 6 months

Protect from frost, sunlight, moisture and dirt.

Store at temperatures from 5 °C to max. 30 °C.

**Packaging:**

Drum 100 l

Other delivery quantities on request

**Safety Rules:**

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).

When used, ensure good ventilation (5 to 15 air exchange per hour) or use exhaust device.

Do not breathe spray.

The product is inflammable. Therefore please keep away from open fire and other ignition sources during application.

**Assistance:**

Please contact our Technical Application Centre.

**Industrial use:**

Recommended frequency and duration of use:

Roll/swipe: 480 minutes/day

Spraying: with local suction

**Environmental Exposure:**

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or the sewage system.

Toxic to aquatic life with long lasting effects.