

# BPB Lichen Remover

Lichen remover  
Product No.: 02000-206x

## Product Information:

### Properties:

– for removing lichens

### Application:

on mineral and alkali-proof surfaces as natural stone, concrete, plaster or clinker bricks

Lichens grow in excellent air quality and can live nearly forever. The symbiotic connection between algae and fungus resists to the usual cleaning methods. The BPB lichen remover has especially been developed for the gentle, acid-free and thus non-destructive removal of this soiling. Treating the surfaces with lichen remover will destroy the growth of lichens and avoid any further formation of roots and spores.

The surface to be treated must be pre-wet before applying the cleaner. The lichen remover is sprayed or applied liberally onto the damp surface. After a time of reaction of max. 45 min. the dead lichens are loosened with a brush or similar from the surface which is then rinsed with plenty of clear water. This procedure can be repeated according to the degree of soiling.

Do not dispose of with the household waste! Dispose of product residues in hazardous waste dump or collection points for hazardous substances! Do not allow the material to enter the drainage system, water courses or soil. Stir the product before use.

### Please note:

Use biocidal products carefully. Always read the label and product information before use. Generally conduct a preliminary test to avoid changes in colour of the surface to be treated and to determine the needed quantity.

### Quantities to use:

Recommended dosage: 100 ml/m<sup>2</sup>

### Composition:

1.0 % Quaternary ammonium compounds (BAC C12-16)

Do not use in direct sun and <+15 °C.

### Specifications:

Appearance: liquid  
Colour: clear to slightly yellowish  
Density: 1.19 ± 0.03 g/ml

### Approval No.:

BAuA-Reg.-No.: N-68521

### Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 5 years.

The product should be stirred before use.

**Packaging:**

container 1,000 kg, drum 210 kg, can 20 kg  
Please ask for further package sizes.

**Safety Rules:**

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).

During cleaning work ensure good ventilation (5 to 15 air changes per hour) or exhaust suction device to use.

Keep out of the reach of children. In case of contact with skin, wash immediately with plenty of water and soap.

Do not mix with other products. Not for indoor use.

**Restriction of use for SWITZERLAND**

From 1.12.2020, green film removers may only be used in Switzerland for applications on facades, irrespective of the active substance they contain (ChemRRV of 17.4.2019; Annex 2.4, Number 4).

Use on roofs and terraces, on storage areas, on and along roads and railways is prohibited from that date.

**Assistance:**

Please contact our Technical Application Centre.

**Industrial use**

Recommended frequency and duration of use:

480 minutes per day

5 days per week

**Commercial use**

Daily amount: 130 kg

Recommended frequency and duration of use:

480 minutes per day

5 days per week

**Consumers**

Recommended frequency and duration of use:

Amount used per cleaning operation: 0.5 l

Duration: 1 minute

Frequency: 150 times per year