

# BPB<sup>®</sup> Oil Remover

Oil Stain Remover

## Industrial use

Product No.: 320041000 ! ATTENTION: NEW PRODUCT NUMBER FROM 2024 !

Product No. until 2023: 329010028

## Product Information:

### Sustainability Assessment:

Soil contamination with oil is one of the most common contaminated sites in soil. Even small amounts of oil can damage soil and water.

### Properties:

– free of aromatic compounds and biodegradable

### Application:

for all cement-bonded building materials, clinker bricks, floor pavement as well as natural and interlocking paving blocks

A detergent specially developed for removing all types of oil stains. Due to the high dissolving power, only small amounts of active ingredient are required to remove oil stains. The detergent is based on natural products, is aromatic-free and biodegradable.

The detergent is applied neat to the surface to be cleaned.

The detergent is applied with a brush, brush or spray device, depending on the cleaning purpose. After a short exposure time, the detergent can be removed with water (and/or a cloth).

Always carry out a preliminary test to determine the compatibility of the substrate to be treated and to determine consumption.

### Ingredients:

>= 30% D-Limonene

5 -< 15% nonionic surfactants

### Quantities to use:

Depending on application up to optimum cleaning effect. The application can be repeated as often as required until perfect cleaning.

### Specifications:

Appearance: liquid  
Colour: green blue  
Density: 0.88 ± 0.03 g/ml  
Flash point: approx. 58,5 °C

### Storage:

Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months  
Protect from frost, direct sunlight and contamination.

### Packaging:

Bottle 600 ml

**Safety Rules:**

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).

When cleaning, ensure good ventilation (5 to 15 air changes per hour) or use suction devices.

No open flames and light during spraying. Keep away from ignition sources. Test first if used on plastics.

**Assistance:**

Please contact our Technical Application Centre.

**Industrial use:**

Recommended frequency and duration of use:

Roll/Sweep/Spray: 480 minutes/day with local exhaust ventilation

**Environmental Exposure:**

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or the sewage system.