

BPB SYSTEM CLEANER Complete

System cleaner
Product No.: 02000-2090

Product Information:

Properties:

– removes green grows

Application:

on porous mineral surfaces as natural stone, concrete, plaster or tiles

BPB SYSTEM CLEANER Complete is a concentrated detergent. The cleaning effect can be seen after few hours. Applying BPB SYSTEM CLEANER Complete to the green surfaces removes moss, mould, lichen and algae due to the self-acting depth-effect formula. Avoid contact to plants. If plants get in contact with this product, rinse with a lot of water. May not enter fish ponds.

Take care of a thorough and complete moistening. When applying the product the surface should be dry to avoid a dilution of the substance.

To clean normal growth of moss, mould, lichen and algae BPB SYSTEM CLEANER Complete is diluted with water in a ratio of 1:3. The surfaces to be treated must be absolutely dry. BPB SYSTEM CLEANER Complete is applied generously with a brush or spray to the dry surface to be treated. Do not use in plantings. Green plant parts which have come in contact with the product solution will turn brown. Generally conduct a preliminary test to avoid changes in colour of the surface to be treated and to determine the needed quantity.

Quantities to use:

To clean surfaces apply approx. 100 to 200 g/m².

The product has an excellent compatibility of materials. In case of over-dosage white coatings can occur which will disappear after some time by weathering. Use a higher dilution (1:5) for the next application. On sensitive materials as e. g. marble test a small hidden area to confirm suitability. Do not apply on artificial resin slabs. In case of contact with copper, zinc, brass or artificial resin slabs durable material discolourations can occur which cannot be removed.

Specifications:

Appearance: liquid
Colour: colourless
Density: 1.00 ± 0.02 g/ml

Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 5 years.

Packaging:

can 20 kg and 5 kg, bottle 1 kg
Please ask for further package sizes.

Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).

During cleaning work ensure good ventilation (5 to 15 air changes per hour) or exhaust suction device to use.

Do not mix with other products. Do not use inside.

Restriction of use for SWITZERLAND

From 1.12.2020, green film removers may only be used in Switzerland for applications on facades, irrespective of the active substance they contain (ChemRRV of 17.4.2019; Annex 2.4, Number 4).

Use on roofs and terraces, on storage areas, on and along roads and railways is prohibited from that date.

Assistance:

Please contact our Technical Application Centre.

Industrial use

Recommended frequency and duration of use:

Roll/paint: < 4 hours/day

220 days/year

spraying: with lokal exhaust

Commercial use

Recommended frequency and duration of use:

Rolling / painting: 4 hours / day

Spraying: <15 min / day

Consumers

Recommended frequency and duration of use:

Amount used per cleaning operation: 0.5 l

Duration per day: 4 hours

Frequency of use: 5 times per year