

# BPB® Special Care

Preservative agent for surface refined concrete slabs

## Consumers

Product No.: 340705000 ! ATTENTION: NEW PRODUCT NUMBER FROM 2024 !

Product No. until 2023: 349020062

## Product Information:

### Properties:

- water-, oil- und dirt-repellent
- permeable to water vapour, non-yellowing and UV-resistant
- CO<sub>2</sub>-barrier

### Application:

Care of sealed and already laid surface refined concrete slabs

The care product is used on the dry side. Applied as a care product, the dirt and water-repellent effect of the laid, surface-refined tiles is refreshed and gives the tiles a neat appearance. Light, superficial scratches are removed.

The substrate must be clean, dry, free of grease and any substance that could impede the penetration of the product.

The product is applied in one or two passes (wet on wet).

In the case of less absorbent surfaces, no excess product may remain on the surface. This can make the surface scratch sensitive. The order quantity is to be reduced.

**Attention:** Only apply to water-draining, bedded surfaces (without moisture build-up).

The treated area can be walked on after 8 hours. Rainproof after 24 hours.

To assess the final effect a testing site on the surface which is representative for the final application is imperative.

Stir well before use. Close the container well after each use; the product tends to form a skin on contact with air.

Pour tous les domaines d'utilisation avec des charges de marche normales et des charges de conduite faibles. Le film de revêtement durci n'est pas durablement résistant aux plastifiants. Par conséquent non recommandé pour les parkings, les garages, etc.

### Quantities to use:

30 - 80 g/m<sup>2</sup>

Depending on the application, depending on the absorbency of the panels.

The specified quantities are approximate values because the actual applied quantity does not only depend on the surface structure, but also on the absorbency of the surface.

Avoid direct sunlight or the generation of dust during processing. Do not apply if rain is forecast within the next 4 hours. The surface temperature should be at least 10 °C and max. 30 °C. Tools shall thoroughly be cleaned with water or put into water immediately after use. Once dried product can hardly be removed.

### Specifications:

Appearance:	liquid
Colour:	milky
Density:	1.00 ± 0.02 g/ml

**Storage:**

Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months  
Protect from frost, direct sunlight and contamination.  
The storage temperature must not exceed 30 °C. Stir before use.

**Packaging:**

Can 20 l, Can 5 l, small units, Drum, Containers  
Other delivery quantities on request

**Safety Rules:**

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).

When used, ensure good ventilation (5 to 15 air exchange per hour).

**Assistance:**

Please contact our Technical Application Centre.

**Industrial use:**

Recommended frequency and duration of use:  
Roll/Sweep: < 480 minutes/day

**Commercial use:**

Recommended frequency and duration of use:  
Roll/Sweep: < 240 minutes/day

**Consumers:**

Recommended frequency and duration of use:  
Quantity used per use: 1.4 kg  
Duration per day: 240 minutes  
Frequency of use: 4 times per year

**Environmental Exposure:**

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or the sewage system.