

# COLORaktiv 2000 SR (LP)

Sedimentation-reducing air-entraining agent according to EN 934-2:T5  
Product No.: 200004010

## Product Information:

### Properties:

- reduces efflorescence
- improves the freeze-thaw resistance
- stabilising effect
- intensifies the colouring
- avoids sticking to the ram

### Application:

concrete products

Is added together with the aggregates or, if the aggregates are highly absorbent, to the finished concrete mix.

### Dosage:

Recommended dosage: 0.2 - 0.4 ml/kg of the binding agent content

The quantity to use depends on the required effect, cement grade and type of concrete. Please call us for technical advice.

Prior to use, a suitability test according to EN 206-1 or any applicable standards or norms relevant in your country is required.

### Specifications:

Appearance: liquid  
Colour: green  
Density: 1.03 ± 0.02 g/ml

### Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months.

### Packaging:

container approx. 1000 kg, drum approx. 210 kg, can approx. 20 kg  
Please ask for exact package sizes.

### Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).  
When used, ensure good ventilation (5 to 15 air exchange per hour).

### Assistance:

Please contact our Technical Application Centre.

### Industrial use

Recommended frequency and duration of use:

8 hours/day  
200 days/year



Blomberg GmbH & Co. KG

Beton- und Prüftechnik Blomberg GmbH & Co. KG

Industriestraße 19 | D-32825 Blomberg  
Tel. +49 5235 963-0 | Fax +49 5235 963-230  
info@remei.de | www.remei.de

Niederlandstraße 11 | D-32825 Blomberg  
Tel. +49 5235 99459-0 | Fax +49 5235 99459-20  
kontakt@bpb-info.de | www.bpb-info.de