

ECO Terrassen und Balkon Reiniger

Easily biodegradable special cleaner

Consumers

Product No.: 320032000

Product Information:

Properties:

- powerful and sustainable
- highly effective and natural acid combination

Application:

for acid-resistant natural and artificial stones.

slate, granite or quartz, ceramic surfaces such as clinker bricks, split tiles, glazed and unglazed tiles or concrete blocks

balconies, terraces, walkways and similar.

Removes impurities, lime deposits and stubborn dirt

Sustainability Assessment:

Surfactants 100% from renewable raw materials

Dosage:

Pure or diluted 1:3

Application time approx. 5 minutes

Yield: 5 - 7 m² Application-related until the optimum cleaning effect is achieved.

The product is not suitable for acid-sensitive surfaces and nickel and chrome parts. Take special care with limestone, e.g. marble, etc. For enamel, clean only briefly and rinse immediately. Protect metal from corrosion immediately after cleaning (grease, e.g. with release and care oils).

Processing:

Apply cleaner undiluted or diluted 1:3 to the pre-wetted surface and allow to react briefly but do not allow to dry.

Rework with a sponge or scrubbing brush and rinse thoroughly with water.

Always carry out a preliminary test to determine the compatibility of the substrate to be treated and to determine the consumption.

Ingredients:

Fragrances

Specifications:

Appearance: liquid

Colour: colorless

Density: 1.04 ± 0.02 g/ml

pH value: approx. 3

Storage:

Under normal storage conditions (closed, 20 °C) minimum shelf life 24 months.

Protect from frost, sunlight and contamination.

Packaging:

Canister 20 l, Canister 5 l, Small containers

Further delivery quantities on request

Safety Rules:

See EC safety data sheet.

Always use the product only with suitable protective gloves (EN 374) and goggles (EN 166).

During cleaning operations, ensure good ventilation (5 to 15 air changes per hour) or use extraction equipment.

The product must not be sprayed.

Assistance:

Please contact our Technical Application Centre.

Industrial use:

Recommended frequency and duration of use:

Rolling/painting: 480 minutes/day with local exhaust.

Commercial use:

Recommended frequency and duration of use:

Rolling/brushing: 60 minutes

5 days/week

Consumers:

Recommended frequency and duration of use:

Amount used per cleaning operation: 0.5 l

Duration per day: 240 minutes

Environmental Exposure:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or sewage system.