

ECOtrenn E

Mineral oil-free separating agent for hard-wood pallets
Product No.: 310001000

Product Information:

Properties:

- preserves the wood and extends the shelf-life
- durable water-oil emulsion
- environmentally friendly preserving emulsion

Application:

pallets for block machines

It is to be expected that the product can be assessed as "easily biodegradable" due to the used ingredients.

Primarily, a daily treatment is important especially on brand-new pallets. We recommend applying ECOtrenn (E) automatically with a suitable spray system. New wooden moulds should be treated at least 10 min. prior to use.

Quantities to use:

20 - 50 g/m², depending on the type and absorbency of the mould

Specifications:

Appearance: liquid
Colour: white
Density: 0.99 ± 0.02 g/ml

Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months.

Packaging:

container 1000 l, drum 210 l, can 20 l
Please ask for further package sizes.

Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).
When used, ensure good ventilation (5 to 15 air exchange per hour) or exhaust suction device to use.
Do not breathe spray.

Assistance:

Please contact our Technical Application Centre.