REMEI BPB GmbH & Co. KG
BETRA GmbH

Edition: 08/22
Reference: Separating and Preservative Agent

ECOtrenn E

Mineral oil-free separating agent for hard-wood pallets
Industrial use
Product No.: 310001000

Product Information:

Sustainability Assessment:
Vegetable oil based emulsion
> 95% of the active ingredient content from renewable raw materials

Properties:
– preserves the wood and extends the shelf-life
– durable water-oil emulsion
– environmentally friendly preserving emulsion

Application:
pallets for block machines

Release agents have hardly any effect on the total of CO_2 emissions and the greenhouse gases produced in the production process.
This effect is attempted to be balanced by using sustainable raw materials.

It is to be expected that the product can be assessed as "easily biodegradable" due to the used ingredients.

Daily treatment is important initially, especially with new production boards. It makes sense to apply the release agent automatically with a suitable spray device.

New wooden moulds should be treated at least 10 min. prior to use.

Quantities to use:
20 - 50 ml/m²
depending on the type and absorbency of the mould

Specifications:

Appearance:	liquid
Colour:	white
Density:	0.99 ± 0.02 g/ml

Storage:
Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months
Protect from frost, direct sunlight and contamination.

Packaging:
Container 1000 l, Drum 210 l, Can 20 l
Other delivery quantities on request

Safety Rules:
See EC safety data sheet.
The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).

When used, ensure good ventilation (5 to 15 air exchange per hour) or use exhaust device.
Do not breathe spray.

Assistance:
Please contact our Technical Application Centre.

Industrial use:
Recommended frequency and duration of use:
480 minutes/day with local exhaust

The user should consider this information as our recommendation for the application of our products. Prior to use, we strongly recommend to conduct preliminary tests.

Environmental Exposure:
Do not allow undiluted product or large quantities of it to reach ground water, water bodies or the sewage system.