

# ECOtrenn N

Separating agent for non-absorbing moulds  
Product No.: 310011000

## Product Information:

### Properties:

- mineral oil-free
- corrosion inhibiting and preserving

### Application:

for all types of moulds  
for heated moulds up to 60 °C

It is to be expected that the product can be assessed as "easily biodegradable" due to the used ingredients.

ECOtrenn N is applied with a spray system (wide jet) to the mould in a very thin layer. The mould should be dry and clean to obtain the full effect of the thin layer. The product is delivered ready for application and may not be diluted. Do not allow product to get into the environment uncontrolled.

### Quantities to use:

10 - 25 g/m<sup>2</sup>, depending on the type and absorbency of the mould

Vegetable oils can sometimes have a significant influence on the resistance of certain rubber seals. To be on the safe side, we recommend checking the compatibility of the parts that come into contact before use.

### Specifications:

Appearance: liquid  
Colour: amber  
Density: 0.87 ± 0.02 g/ml

### Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months.

### Packaging:

container 1000 l, drum 210 l, can 20 l  
Please ask for further package sizes.

### Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).  
When used, ensure good ventilation (5 to 15 air exchange per hour) or exhaust suction device to use.  
Do not breathe spray.

### Assistance:

Please contact our Technical Application Centre.

### Industrial use

Recommended frequency and duration of use:  
up to 8 hours / day with local exhaust