

OIL REMOVER SPRAY

Oil Stain Remover

Properties:

- biodegradable
- low vapour pressure
- safe application

Application:

for all cement-bonded building materials, clinker bricks, floor pavement as well as natural and interlocking paving blocks

ÖLENTFERNER-SPRAY (OIL REMOVER SPRAY) is a detergent which has especially been developed for removing all kinds of oil stains. Due to the high detaching power of ÖLENTFERNER SPRAY (OIL REMOVER SPRAY) only very small quantities of active ingredients are needed to remove oil stains. ÖLENTFERNER-SPRAY (OIL REMOVER SPRAY) is based on natural products, free of aromatic compounds and biodegradable. Due to the low vapour pressure ÖLENTFERNER-SPRAY (OIL REMOVER SPRAY) causes inferior air pollution only. The high ignition point offers an optimum safety during application.

ÖLENTFERNER-SPRAY (OIL REMOVER SPRAY) is sprayed undiluted with a spray system directly to the object to be cleaned. After a short time of reaction ÖLENTFERNER-SPRAY (OIL REMOVER SPRAY) can be removed with water (and/or with a cloth).

Consumption:

Depending on application up to the optimum cleaning effect. The application can be repeated as often as required until perfect cleaning.

Generally conduct a preliminary test to avoid changes in colour of the surface to be treated.

Specifications:

Appearance: Aerosol
Colour: whitish

Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months. Shake well before use.

Packaging/Packages:

spray can at 500 ml
exact delivered quantity on request

Safety Rules:

See EC Safety Data Sheet.

The can is under pressure. Do not expose to sunlight and temperatures >50 °C. Do not open by force or combust after use. Do not spray against flames or flowing objects. Keep away from sources of ignition. Do not smoke. Keep out of reach of children. Use in well-ventilated areas only. To avoid flammable vapour-air-mixture, take care of sufficient ventilation. Do not breathe aerosol. Avoid contact with eyes and skin. Do not empty into drains. Extremely flammable. Irritating to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness. Dispense only if completely empty. Contains >30 % aliphatic hydrocarbon. Corresponds to the European Regulation on Detergents (EG) 648/2004.

Wear protective gloves. Eye protection recommended.

Assistance:

Please contact our Technical Application Centre.