

REBA Schalwachs (wax for moulds)

Separating paste based on mineral oil for all types of moulds
Product No.: 310016000

Product Information:

Properties:

- excellent sticking to vertical moulds
- the concrete does not rub off the separating agent from the mould
- resistant to rain

Application:

for all types of moulds

By applying REBA-Schalwachs (wax for moulds) steel reinforcements which have to be bended off the mould level after release, do not connect with the surrounding concrete.

REBA-Schalwachs is applied to the mould undiluted with a soft cloth or sponge as thin and homogeneous as possible. The mould should be dry and clean to provide for the entire effect of the formed film. Do not allow product to get into the environment uncontrolled.

Quantities to use:

25 - 50 g/m², depending on the type and absorbency of the mould

Specifications:

Appearance: paste
Colour: white
Density: 0.86 ± 0.02 g/ml

Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 24 months.

Packaging:

plastic bucket 30 l

Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166). When used, ensure good ventilation (5 to 15 air exchange per hour) or exhaust suction device to use. Do not breathe spray.

Assistance:

Please contact our Technical Application Centre.

Industrial use

Recommended frequency and duration of use:
up to 8 hours / day with local exhaust