

REBA Schalwachs (wax for moulds)

Separating paste based on mineral oil for all types of moulds

Industrial use

Product No.: 310016000

Product Information:

Properties:

- excellent sticking to vertical moulds
- the concrete does not rub off the separating agent from the mould
- resistant to rain

Application:

for all types of moulds

As a result of the application, steel inserts, which have to be bent out of the formwork level after stripping, do not form a connection with the surrounding concrete.

The release agent is applied to the mould undiluted with a soft cloth or sponge as thin and homogeneous as possible.

The mould should be dry and clean to provide for the entire effect of the formed film.

Quantities to use:

25 - 50 ml/m²

depending on the type and absorbency of the mould

Specifications:

Appearance: paste
Colour: white
Density: 0.86 ± 0.03 g/ml

Storage:

Under normal storage conditions (closed container, 20 °C) minimum shelf-life 24 months
Protect from frost, direct sunlight and contamination.

Packaging:

Plastic Bucket 30 l

Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).

When used, ensure good ventilation (5 to 15 air exchange per hour) or use exhaust device.

Do not breathe spray.

Assistance:

Please contact our Technical Application Centre.

Industrial use:

Recommended frequency and duration of use:

480 minutes/day with local exhaust

Environmental Exposure:

Do not allow undiluted product or large quantities of it to reach ground water, water bodies or the sewage system.