

# REBA Wachstrennmittel (wax for moulds)

Separating agent for all moulds  
Product No.: 310015000

## Product Information:

### Properties:

- good visible surfaces
- for sharp edges and profiles
- the concrete does not rub off the wax emulsion from the mould

### Application:

for all types of moulds

REBA-Wachstrennmittel (wax for moulds) is suitable both as a release agent for factory use in the precast industry and for wooden moulds. Due to the use of REBA Wachstrennmittel (wax for moulds), steel inserts that have to be bent out of the formwork plane after striking do not form a bond with the surrounding concrete.

REBA-Wachstrennmittel is applied to non-absorbent formwork undiluted with a cloth or sponge as thinly and evenly as possible onto the formwork. The mould should be dry and clean to provide for the entire effect of the formed film. With wooden moulds, regular treatment is initially important, especially with new underlay boards. It makes sense to apply the release agent automatically with a suitable spraying device. Gradually a protective wax layer builds up. This is evident from the greatly reduced absorbency of the boards.

### Quantities to use:

20 - 60 g/m<sup>2</sup>, depending on the type and absorbency of the mould

### Specifications:

Appearance: liquid  
Colour: beige  
Density: 0.99 ± 0.02 g/ml

### Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months.

### Packaging:

container 1000 l, drum 210 l, can 20 l  
Please ask for further package sizes.

### Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).  
When used, ensure good ventilation (5 to 15 air exchange per hour) or exhaust suction device to use.  
Do not breathe spray.

### Assistance:

Please contact our Technical Application Centre.