

REBAnit A

Moss and algae removing agent
Product No.: 320003000

Product Information:

Properties:

– for removing algae, mildew and moss

Application:

porous mineral surfaces

The cleaner is used on porous mineral surfaces such as natural stone, concrete, plaster or brick. The surfaces to be worked on must be dry.

To remove usual phyllomania REBAnit A has to be diluted with water in the ratio 1:3 and applied by saturated spraying or brushing to the dry surface. After approx. 3 to 5 days the dry algae can easily be removed with a besom. In case of intensive growth the procedure has to be repeated or a stronger REBAnit A concentration has to be chosen. Do not dispose of with the household waste! Dispose of product residues in hazardous waste dump or collection points for hazardous substances! Do not allow the material to enter the drainage system, water courses or soil. Keep out of reach of children. Wear chemical resistant gloves. In case of contact with the skin immediately rinse with plenty of water and soap.

Please note:

Use biocidal products carefully. Always read the label and product information before use.

Composition:

2.9% Quaternary ammonium compounds (BAC C12-16)

Generally conduct a preliminary test to avoid changes in colour of the surface to be treated and to determine the needed quantity.

Quantities to use:

For the application on surfaces apply 100 - 200 g/m².

Specifications:

Appearance: liquid
Colour: blue
Density: 1.00 ± 0.02 g/ml

Registration number:

BAuA reg. no.: N-68514

Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 5 years.

Packaging:

container 1,000 kg, drum 210 kg, can 20 kg
Please ask for further package sizes.

**Safety Rules:**

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166). During cleaning work ensure good ventilation (5 to 15 air changes per hour) or exhaust suction device to use.

Do not mix with other products

Restriction of use for SWITZERLAND

From 1.12.2020, green film removers may only be used in Switzerland for applications on facades, irrespective of the active substance they contain (ChemRRV of 17.4.2019; Annex 2.4, Number 4).

Use on roofs and terraces, on storage areas, on and along roads and railways is prohibited from that date.

Assistance:

Please contact our Technical Application Centre.

Industrial use

Use biocidal products carefully. Always read label and product information before use.

Commercial use

Use biocidal products carefully. Always read the label and product information before use.

Consumers

Use biocidal products carefully. Always read the label and product information before use.