

# REBAtrenn 2003

Separating agent for all types of moulds  
Product No.: 310020000

## Product Information:

### Properties:

- separating agent for all types of moulds
- does not build up, odourless

### Application:

for all types of moulds  
concrete products  
precast concrete elements  
coffered ceilings and filigree pieces

Spray or brush evenly on cleaned and as dry a surface as possible. Loading can be effected immediately after application or later. Protect against heavy rain. Concrete surfaces that are to be plastered should not have any moulding oil residues. Do not allow product to get into the environment uncontrolled.

### Quantities to use:

30 - 40 g/m<sup>2</sup> for absorbing wooden moulds  
15 - 30 g/m<sup>2</sup> for steel and plastic moulds

### Specifications:

Appearance: liquid  
Colour: colourless to slightly yellowish  
Density: 0.82 ± 0.02 g/ml

### Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months.

### Packaging:

Nein

### Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166). When used, ensure good ventilation (5 to 15 air exchange per hour) or exhaust suction device to use. Do not breathe spray.

### Assistance:

Please contact our Technical Application Centre.

### Industrial use

Recommended frequency and duration of use:  
up to 8 hours / day with local exhaust