

REBAtrenn E 20

Water-dilutable separating agent for wooden pallets and wooden moulds
Product No.: 310008000

Product Information:

Properties:

- avoids formation of air pores and cement film
- does not form any residues
- stable water-oil emulsion
- water dilutable (1:5)

Application:

for all wooden moulds
hard wood fibre supporting boards
pallets and shutter panels

Primarily a daily treatment is important, especially on brand-new pallets. We recommend applying REBAtrenn E 20 automatically with a suitable spray system. The wooden moulds should be treated at least 15 min. prior to use. Do not allow product to get into the environment uncontrolled.

Quantities to use:

20 - 50 g/m², depending on the type and absorbency of the mould

Specifications:

Appearance: liquid
Colour: white
Density: 0.97 ± 0.02 g/ml

Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 6 months.

Packaging:

container 1000 l, drum 210 l, can 20 l
Please ask for further package sizes.

Safety Rules:

See EC safety data sheet.
The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166).
When used, ensure good ventilation (5 to 15 air exchange per hour) or exhaust suction device to use.
Do not breathe spray.

Assistance:

Please contact our Technical Application Centre.

Industrial use

Recommended frequency and duration of use:
up to 8 hours / day with local exhaust