

REBAtrenn Universal

Mineral oil-based separating agent
Product No.: 310024000

Product Information:

Properties:

- efficient separating agent
- does not build up, odourless

Application:

for all types of moulds
precast concrete elements

REBAtrenn Universal is applied by spraying or brushing to a clean, dry surface. Loading can be effected immediately after application or later. Protect against heavy rain. Concrete surfaces that are to be plastered should not have any moulding oil residues. Best results are obtained by using absorbing wooden moulds. Do not allow product to get into the environment uncontrolled.

Quantities to use:

15 - 50 g/m², depending on the type and absorbency of the mould

Specifications:

Appearance: liquid
Colour: amber
Density: 0.84 ± 0.02 g/ml

Storage:

Protect against frost and dirt. Under normal storage conditions (closed container, 20 °C) minimum shelf-life 12 months.

Packaging:

container 1000 l, drum 210 l, can 20 l
Please ask for further package sizes.

Safety Rules:

See EC safety data sheet.

The product should only be used with suitable protective gloves (EN 374) and safety goggles (EN 166). When used, ensure good ventilation (5 to 15 air exchange per hour) or exhaust suction device to use. Do not breathe spray.

Assistance:

Please contact our Technical Application Centre.

Industrial use

Recommended frequency and duration of use:
up to 8 hours / day with local exhaust